

D2012 Plus

High Speed Mini Centrifuge

Features

- · Pulse operation for fast and convenient quick spins
- Speed up to $15000 \text{rpm} (15100 \times \text{g})$
- · Brushless DC motor drive quickly to the target speed
- Smooth and quiet operation (noise ≤54dB)
- · Automatic door lock and over-speed detection
- · Passed rigorous explosion-proof test, certified with CE, cTÜVus, FCC



Microcentrifuges are mainly used in molecular biology laboratories for Plasmid extraction; Nucleic acid purification; Pre-sequencing processing and other applications including extracting of DNA/RNA samples, sedimentation biological components, biochemical and chemical analyses of microsamples.

| Specifications | D2012 plus |
|----------------------------------|--|
| Max. Speed | 15000rpm(500-15000rpm), increment: 100rpm |
| Max. RCF | 15100 × g, increment: 100 × g |
| Speed Accuracy | ± 20rpm |
| Rotor Capacity | 0.2mL/ 0.5 mL/ 1.5 mL/ 2 mL × 12 |
| Run Time | 30sec-99min/Continuous |
| Acceleration/Braking time | 11s↑/9s↓ |
| Driving Motor | Brushless DC motor |
| Safety Devices | Door interlock, Over-speed detection, Over-temperature detection, Automatic internal diagnosis |
| Power | Single-phase, AC100V-240V, 50Hz/60Hz, 3A100W |
| Noise level | ≤54dB |
| $Dimension[D \times W \times H]$ | 255 × 245 × 140mm |
| Weight | 6kg |
| Certification | EMC CE FCC ICES cTÜVus CB |
| Other functions | Speed/RCF switch,Short-time run function,sound-alert function |



Available rotors



Cat.NO.19400010 A12-2P

for D2012plus only

Max. speed: 15000rpm Max. RCF: 15100 × g Rotor capacity:

 $2mL/1.5mL \times 12,0.2mL \times 12,0.5mL \times 12$ Rotor material: High strength plastic Available rotor adapters: A02P2,A05P2

Available adapters

A02P2 Cat. No.19500001

0.2mL rotor adapter Used with A12-2, A12-2P, AS24-2 and A24-2P rotors 24 pcs/pk



A05P2 Cat. No.19500002

0.5mL rotor adapter Used with A12-2,A12-2P, AS24-2 and A24-2P rotors 24 pcs/pk

